



VEHICLE TRACKING SYSTEM GT100





Operating and Installation Instructions

Safety Notes

This device has been manufactured according to established safety guidelines. However, dangers may still occur if the safety notes in this manual is not observed. This manual is intended to familiarize the user with the device's important functions. Read this carefully, prior to using the device. Keep this manual in an easily accessible location. In addition of the devices used in conjunction with this device.

Attentions

- This device is intended for installation and operation in a vehicle with 12V and 24V vehicle system voltage.
- Keep the device away from children.
- Keep the device away from flammable areas or liquids.
- The device should be stored in dry and low humidity place.
- Ensure the car battery is fully charged.
- Weak signal or signal interference of device can arise from obstacle locations such as underground parking.

 For abnormalities, please refer to the "Troubleshooting" section. Consult with Blaupunkt dealer for further assistance, in case if the problem cannot be resolved.

This manual may be updated from time to time without any notice. Visit www.blaupunkt.com/ase for latest info.

Disclaimer

In no event shall Blaupunkt be liable for any direct, indirect, punitive, incidental, special consequential damages to property or life and whatsoever arising out of or connected with the use or misuse of our products.

USA & CANADA: This product is not intended for sale in the United States and Canada. If purchased in the U.S. or Canada, this product is purchased on as-is basis. Warranty, whether expressed or implied is provided in the U.S. or Canada.

Blaupunkt does not warrant the performance of the local telecommunication network used with our product. It is recommended to test for network compatibility prior to purchase.

STRUCTURE & FUNCTIONS



Functions

- 1. Indicator light of GSM
- 2. Indicator light of GPS
- 3. Switch (On/Off)
- 4. SIM card slot
- 5. Light sensor

SPECIFICATIONS

- Operating Voltage : DC 9V-36V
- Current : 10mA
- Navigation System : GPS
- · Location Accuracy : Up to10 meters
- GSM Frequency : 850/900/1800/1900MHz
- Internet Protocol : TCP
- Working Temperature : -25°C ~ +75°C
- Storage Temperature : -40°C ~ +85°C
- Standby Battery : 0.5 Hours
- Dimension (LxWxH): 78.5x23x12mm

FUNCTION LIST OF THE DEVICE

Functions	Details	Descriptions	
Vehicle	Acc On/ Off	Uploaded data include the Acc On/	
Status		Off status each time in dynamic view.	
Detection			
	External Power	When the vehicle voltage is <5V,	
	Disconnection	vehicle battery consumption is	
		stopped. When the backup battery	
		of device is depleted, the tracking	
		function will be disconnected.	
	Low External	Vehicle battery voltage is between	
	Battery	5V to 10V. It is an indicate that the	
		vehicle battery is low.	
Alarm	External Power	Power is supplied to the device.	
Notification	Supply		
	External Power	Power supply has been disconnected	
	Disconnection	from the device.	
	Enter Fence	The vehicle enters the defined area	
		set by user.	
	Leave Fence	The vehicle leaves the defined area	
		set by user.	
	Speeding Start	Vehicle speed exceeds value set.	
		Default is 120km/hr for 10 seconds.	
	Speeding End	Vehicle speed is below value set after	
		speeding is detected.	



TROUBLESHOOTING

If any of the following problem occur, please resort to Troubleshooting for the possible solutions. Consult Blaupunkt authorized dealer if problem persist.

Problems	Possible Causes	Solutions
Weak or no	GPS tracking device is	Check the installation location
GPS signal	not positioned properly.	of the device.
		Ensure it is not being shielded
		by metal.
The device is	SIM card has run out	Top up the SIM card.
not respond-	of credit.	
ing to SMS	Improper installation of	Check whether the SIM card
commands	SIM card.	has been slotted correctly.
		Check that the SMS command
		is correct.

OPERATION INSTRUCTION

 Remove device cover and insert the SIM card into the SIM card slot and close back the device. (Ensure the SIM card has Internet access)



 Tear off the 3M tape on the back of device and paste it inside the dashboard or car trunk.



DIFFERENT SCENARIO

Indicator of GSM and GPS

System	Indicator Light	Status	Meaning
GSM	Red	Fast Flash	GSM intialising
		Slow Flash	Normal GSM signal
		Long Bright	GPRS online
		No Light	No GSM signal/ No SIM card
GPS	Yellow	Fast Flash	Searching for GPS Signal
		Long Bright	Normal GPS signal
		No Light	No GPS signal/ GPS not
			working

SOFTWARE OPERATION

Mobile Application



Search "Blaupunkt Tracker" on Google Play Store or iOS App Store to download the App.

Home Page

1.0 Menu

- 1.0 Click on the menu button
- 2.0 Click to enter tracking interface.



1.1 Setting



2.0 Tracking

 Click to enter tracking details interface.



2.1 Tracking Details



2.1.1 Playback



2.1.2 Dynamic



2.1.3 Fence



2.1.4 Mileage Analysis & Report



2.1.5 Velocity Analysis & Report



