



BT/USB/AUX – PA1500PRO PROFESSIONAL AUDIO SYSTEM



Professional audio system with Bluetooth and USB player

EAN code: 5901750503696

Features and specifications:

- Bluetooth for audio streaming profile (A2DP) •
- USB player (up to 32 GB)
- MP3 / WMA playback
- Bass / treble adjustment
- Microphone input with echo control
- AUX inputs (XLR, RCA, 6.5 Jack)
- 2 channel class D amplifier
- RMS power: 600 Watt
- Maximum sound pressure level SPL 125 dB
- Wooden bass-reflex enclosure

- Frequency response: 45 Hz 20 kHz
- 1.76 "titanium tweeter with a compression chamber
- 15" woofer with paper cone
- Impedance: 8 Ohms
- Power supply: AC 220 240 V ~ 50/60 Hz
- Dimensions: 440 (W) x 720 (H) x 490 (D) mm
- Weight: 28.33 kg

DISTRIBUTOR:





BT/USB/AUX – PA1500PRO PROFESSIONAL AUDIO SYSTEM

SPECIFICATION

BLUETOOTH

Type of protocol: A2DP

Version: 2.2

Range: Up to 10 m

USB

Version: 2.0 Voltage: 5V 500 mA

Maximum capacity of supported media: 32 GB

Supported audio formats: MP3, WMA

AMPLIFIER

Type: Class D amplifier RMS output power: 600 Watt Number of channel: 2

POWER

Power supply: 220 - 240 V, 50/60 Hz Power consumption: 750 Watt

Power consumption in stand-by mode: < 1 Watt Fuse specification: $5 \times 20/8$ A

SYSTEM SPECIFICATION

System type: 15" self powered, 2 way
Enclosure type: Bass-reflex

Enclosure material: 15 mm painted plywood

Reinforced enclosure: Yes

Type of enclosure connection: Screw, 8 mm metric screws
Speaker mounting method: Metric screws

Tripod socket material: Aluminium

SYSTEM PARAMETERS

Frequency response: 45 Hz - 20 kHz (-10 dB)

Maximum SPL level: 125 dB Crossover frequency: 1,8 kHz Bass / treble adjustment: Yes

WOOFER

Size: 15"

Material: Textured paper
Size and type of the magnet: 6,8" ferrite
The size of the voice coil: 75 mm

Impedance: 8 Ohm Speaker power: 350 Watt

TWEETER

Size and type: 1,76", horn speaker with a compression chamber

Material: Titanium
Size and type of the magnet: 4,8", ferrite
The size of the voice coil: 44 mm
Impedance: 8 Ohm

Speaker power:
Input / Output

Balanced XLR input:

 $6.3 \ mm \ jack \ (microphone \ jack): \qquad 1, integrated \ with \ the \ XLR \ socket$

100 Wat

RCA input 1
XLR output 1
6.3 mm jack output 1

Input signal adjustment: Yes, for each input

Microphone echo adjustment: Yes

PA1500PRO is an uncompromising solution that combines all the advantages of the Power Audio speakers with the possibilities offered by active loudspeakers for professional applications. Extremely high continuous power generated by a two-channel class D amplifier, high efficiency of the speakers used, a bass-reflex enclosure made of heavy-duty material, a wide frequency range combined with the possibilities offered by streaming music files via a Bluetooth module, USB media player, professional XLR connectors and more common RCA and jack together with a display that allows you to control the current playback mode, make this device almost complete and having versatile use both at a small garden party, as well as in a quite large fitness room, or even in a larger outdoor open space.

PA1500PRO - speaker for professional tasks!



DISTRIBUTOR:

2N-Everpol Sp. z o.o. – BLAUPUNKT COMPETENCE CENTER, 02-801 WARSAW, ul. PUŁAWSKA 403A, POLAND Tel.: +48 22 331 99 59, www.everpol.pl, info@everpol.pl