

# EV CHARGING CABLE

TYPE 1 to TYPE 2 Cable



8.0M cable makes for an easy charging experience

**8.0M**



## SPECIFICATIONS:

## 1-PHASE

	<b>A1P16AT1</b>	<b>A1P32AT1</b>
Model No.:	A1P16AT1	A1P32AT1
Working Voltage:	110V ~ 250V	110V ~ 250V
Rated Current:	16A	32A
Insulation Resistance:	>1000MΩ	>1000MΩ
Resistance Voltage:	2000V	2000V
Contact resistance:	Less than 0.5mΩ	Less than 0.5mΩ
Insertion and Extraction Force:	80N<F<100N	80N<F<100N
Main Material:	Thermo Plastic/SiliconRubber/ Copper Alloy	Thermo Plastic/SiliconRubber/ Copper Alloy
Cable Spec.:	3*2.5mm <sup>2</sup> +2*0.5mm <sup>2</sup>	3*6mm <sup>2</sup> +2*0.5mm <sup>2</sup>
Cable Length:	5m	5m
IP-class:	54	54
Fire rating:	UL94 V-0	UL94 V-0
Operating Temperature:	(-30°C ~ 50°C)	(-30°C ~ 50°C)
Net Weight:	1.8 kg	2.5 kg

**DISTRIBUTED BY:**

BLP EV SYSTEMS APS - EDITHS ALLÉ 8, 5250 ODENSE SV, DENMARK