



REVERSE CAMERA

RC 1.0

RC 2.0

RC 3.0



Enjoy it.

CAUTIONS

Safety Notes

This vehicle security system has been manufactured according to established safety guidelines. However, dangers may still occur if the safety notes in this manual is not observed. This manual is intended to familiarize the user with the reverse camera important functions. Read this carefully, prior to using the reverse camera. Reep this manual in an easily accessible location. In addition, do observe the instructions of the devices used in conjunction with this reverse camera.

Attentions

- Assign a mounting location that will not obstruct driver in any circumstances. Or cause injuries to drives and passengers in case of emergency brake or accidents.
- Ensure all wires are connected properly, and that the unit is functioning well before fitting the unit into the mount.
- Any unauthorized installation, disassembly or modification may cause malfunction to the unit and void warranty of the unit.
- Always use only the parts that are included with the units only.
- Do not damage vehicle components when drilling holes for the mount.
- Vehicle may differ from the description provided here. Consult an authorized Blaupunkt dealer or vehicle's manufacturer if the information provided here does not fit your specific installation requirement.
- This unit is applicable for front and reverse camera use. Consult an authorized Blaupunkt dealer during installation.

- · Unit does not record video.
- Avoid automatic car wash or high-pressure water to prevent water and pressure from damaging the camera or causing it to fall off.
- · Do not install this unit near heater outlet.

This manual may be updated from time to time without any notice.


Disclaimer

In no event shall Blaupunkt be liable for any direct, indirect, punitive, incidental, special consequential damages to properly or life and whatsoever arising out of or connected with the use or misuse of our products. USA & CANADA: This product is not intended for sale in the United States and Canada. If purchased in the US. or Canada, this product is purchased on a-si-basis. No warranty, whether expressed or implied is provided in the US. or Canada.


SPECIFICATIONS

Features	RC1.0	RC2.0	RC3.0
CMOS Image Sensor	√	✓	✓
NTSC TV System	✓	✓	✓
Effective Pixels	720 (H) x 480 (V)	720 (H) x 480 (V)	1280 (H) x 720 (V)
750TVL Image Resolution	✓	✓	✓
25/30 Frame Per Second	✓	✓	√
Exposure & Gain Control	✓	✓	✓
1/60~1/100000sec	/	√	√
Electronic Shutter			
Auto White Balance	✓	✓	√
Illumination Min.	0.2 Lux/F	0.2 Lux/F	0.1 Lux/F
Horizontal View	105°H	145°H	160°H
Vertical View	95°V	125°V	140°V
Diagonal View	170°D	170°D	170°D
DC12V Voltage	✓	√	✓
Current	29.3mA	27.1mA	61.5mA
DC9-16V Operating	✓	✓	√
Voltage Range			
Operating Temperature	-20~+70 °C	-20~+70 °C	-20~+70 °C
Storage Temperature	-30~+75°C	-30~+75°C	-30~+75℃
Protection Grade	IP68	IP68	IP68
RCA/4 PIN DIN	✓	✓	✓
Lens	4glass	4glass	5glass

INSTALLATION DIAGRAM




Ground the wire through the exterior body of the vehicle and keep connection intact.



Ground the wire through the exterior body of the vehicle and keep connection intact.


INSTALLATION LOCATION



Attentior

- · Remove protective film from camera lens before use.
- · Take extra precautions when setting up the connection near petrol tank and wires.
- · Connect Red Wire + with reverse light.

INSTALLATION LOCATION



- 1. Pictures are for illustration purpose only, see actual vehicle for accurate installation location.
- Ensure diameter of hole size is correct before drilling.
- 3. Ensure drilling process does not harm the component of the vehicle.
- 4. Assign mounting location that will not obstruct camera view.

- 4


FRONT / REVERSE CAMERA INSTALLATION

FRONT/ REAR VIEW DISPLAY & PARKING LINE

a) Applicable for RC 1.0, RC 2.0

Reverse Camera Wiring (Remove Parking Line)








Reverse Camera

Cut blue wire when using as reverse camera to remove parking line.

Front Camera Wiring (Flip Viewing Display & Remove Parking Line)








Front Camera Cut white & blue wires when using as front camera to flip viewing display & remove parking line.

b) Applicable for RC 3.0

Front Camera Wiring (Flip Viewing Display & Remove Parking Line)





Front Camera
Reconnect white wire when using as
front camera to flip viewing display
& remove parking line.

TROUBLESHOOTING

If any of the following problem occur, please resort to Troubleshooting for the possible solutions. Consult Blaupunkt authorized dealer if problem persist.

Problem	Solution
Display monitor / car radio does not	Restart the display monitor / car radio.
show reverse view when reversing.	
Reverse view does not show even	Examine if the power supplies of the reverse
after restarting the display monitor/	light or the rear car plate light is properly
car radio.	connected.
Reverse view does not show even	Examine if the power supply cables of the
though power supplies of the reverse	reverse light or the rear car plate light is
light or the rear car plate light is	damaged. Repair/replace if the cables are
properly connected.	damaged.



RC 1.0 1 331 19 003 32 02

RC 2.0 1 331 19 004 32 02

RC 3.0

Designed and engineered by Blaupunkt Competence Centre 1 331 19 005 32 02