

LCD TV Product Specification

KTC Model Name: 55FU

Base Model: BCC3-55

Customer Model Name: BLA55ULD01

Platform Model: M-2874T8-ISDB

Brand:

BLAUPUNKT



1.Panel spec (The panel parameters will be somewhat different between different OC, please refer to the corresponding panel specification.)

| | |
|-------------------------------|----------------------------|
| Size | 54.64" diagonal |
| Backlight | DLED direct Type |
| Maximum resolution | 3840×2160 |
| Contrast ratio (Typ) | 1200:1 |
| Response time(Typ) | 9ms |
| Display scale | 16:09 |
| Viewing angle(CR>10) | Typ(H:176° , V:176°) |
| Display Colors | 1.07 B |
| Color Gamut(NTSC) | ≥NTSC 62% |
| LCM Center Luminance of White | Min:250cd/m2; Typ:300cd/m2 |
| Local dimming | nonsupport |
| Uniformity of Luminance | ≥65% |

2.Hardware Information

| | |
|---------------------|--------------------------|
| ATV | PAL M/N; NTSC |
| DTV | ISDB-T |
| CPU Frame | ARM Cortex-CA55*4 |
| GPU | Mail G31 MP2 -High speed |
| RAM(DDR3) | 1.5GB |
| ROM(Flash) | 8GB |
| Audio power(Output) | 8W+8W |
| WIFI(Type) | 2T2R |
| HDMI 1.4 (HDCP 1.4) | - |
| HDMI 2.0 (HDCP 2.2) | 3 |
| USB 2.0 | 2 |
| USB 3.0 | - |
| VGA | - |
| AV In | 1 |
| YPbPr In | - |
| CI | - |

| | |
|--------------------|--------------------------------------|
| PC Audio | - |
| RJ-45 | 1 |
| Earphone | 1 |
| Audio In | - |
| Audio Out | - |
| Video Out | - |
| SPDIF Out | 1 |
| Bluetooth(Version) | YES (V5. 0/4. 2/4. 1/4. 0/3. 0/2. 1) |
| Tuner type | Screw-thread |

3. Software Function

| | |
|--------------------------|-------------------|
| Channel list | YES |
| Channel edit | YES |
| Picture freezing | NO |
| MTS/NICAM | MTS |
| Sleep time setting | YES |
| Teletext | NO |
| PVR | YES |
| EPG | YES |
| V_CHIP/Parental Guidance | Parental Guidance |
| CC(Closed caption) | YES |
| AD(Audio description) | YES |
| TTS(Text to Speech) | NO |
| CI+ | NO |
| DOLBY | YES |
| HDMI-ARC | HDMI-2 |
| HDMI-CEC | YES |
| HDMI-MHL | NO |
| Operation system | webOS 5. 0 |
| OTA | YES |
| Hotel mode | NO |

4. Structure Information

| | |
|------------------------------|---|
| Base model name | BCC3-55 Butterfly wing fixed plastic base |
| Size (without stand) L×W×H | 1228x73x711mm |
| Size (with stand) L×W×H | 1228x261x770mm |
| Size (carton) L×W×H | 1346x124x806mm |
| Net Weight (without stand) | 12. 5kg |
| Net Weight (with stand) | 12. 6kg |
| Gross Weight (without stand) | 16. 0kg |
| Gross Weight (with stand) | 16. 1kg |
| Size (Wall hanging) | 300x200mm |

5.Power Management&Safety&Certificate

| | |
|-------------------|--|
| Power input | 100-240VAc |
| Fire rating | UL94-HB75 |
| Standby power | ≤0.5W |
| Rated power | 130W |
| Working condition | Temperature: 5°C~40°C humidity: 20%~80% atmosphere: 86KPa~106KPa |
| Storage condition | Temperature: -20°C~55°C humidity: 20%~80% atmosphere: 86kPa~106kPa |

6.Accessory

| | |
|-------------------------|------|
| Stand(Optional) | 1PCS |
| Remote control | 1PCS |
| Instruction | 1PCS |
| Warranty card(Optional) | - |
| Battery(Optional) | 2PCS |

Remark 1: The panel parameters will be somewhat different between different panel, please refer to the corresponding panel.
Remark 2: This SPEC is confirmed by KTC and Customer, it will be effective from the dated signed. KTC will control the mass production according to this SPEC and in case all disputes arising from the execution of this agreemen , this SPEC should be prevail.

Signed by PM: _____ Signed by sales Manager: _____

Signed by customer: _____ Date: _____